LKA
INDUSTRIAL SOLUTIONS

Technical Data Sheet

Grease Check Multipurpose

Product Description

Grease Check Multipurpose is the general-purpose working solution of the Grease Check system, prepared from Grease Check Concentrate diluted 1:10 with water. It is intended for routine cleaning of floors, equipment and work surfaces throughout the facility — a mild, pH-neutral cleaner that still cuts light oils and grease and is safe on aluminum, paint, polished stone and other sensitive surfaces.

How It Works

Grease Check cleans through three mechanisms working together: **solvency** — a coupling solvent penetrates and loosens oils, asphalt and baked-on films; **detergency** — a neutralized anionic surfactant lifts and emulsifies the loosened soil into the water phase; and **chelation** — a water conditioning agent breaks down metallic soaps and keeps performance stable in hard water. This combination delivers heavy-duty cleaning at neutral pH, without the caustic attack on aluminum, paint and other sensitive surfaces that high-alkaline degreasers rely on.

Key Features and Benefits

- pH-neutral formula: will not etch or discolor aluminum, galvanized steel, anodized coatings, paint and clear coats, polished stone, or composite surfaces the way caustic and high-alkaline degreasers do.
- Water-based, with no flash point: safe to use around welding, hot work and kitchen equipment where flammable solvents are prohibited.
- Not classified as hazardous under OSHA HazCom 2012; not regulated as a hazardous material for DOT transport.
- Effective on grease, oils, asphalt and bitumen deposits, and baked-on oxidized films.
- Built-in water conditioning: performance is maintained in hard water.
- Contains no caustics, phosphates, or nonylphenol ethoxylates (NPE-free).
- In soak tanks and parts washers, released oils separate and float on standing, allowing oil skimming and extended re-use of the working solution.

Typical Applications

- Daily cleaning of shop, warehouse and plant floors.
- Forklifts, carts and mobile equipment.
- Non-food-contact surfaces in food plants and commercial kitchens.
- Painted and coated surfaces, equipment housings, work benches.
- General facility cleaning where a caustic cleaner is unnecessary or unsafe.

Directions for Use

Preparation: Prepared from Grease Check Concentrate: 1 part concentrate to 10 parts water.

- Apply by mop, wipe, low-pressure sprayer or automatic floor scrubber.
- Allow up to 1–2 minutes of contact time on soiled areas.
- Rinse with water, or wipe clean; floors may be damp-mopped without rinsing in most cases.
- Test in an inconspicuous area before first use on any sensitive or coated surface.

Typical Physical Properties

Appearance	Clear, colorless liquid
Odor	Faint citrus
pH	7.0 - 7.5
Specific gravity	Approx. 1.000

Flash point	None (aqueous solution)
Boiling point	Approx. 212°F (100°C)
Freezing point	Approx. 32°F (0°C) — keep from freezing
Solubility in water	Complete
VOC content	Below 0.5%
D.O.T. shipping	Not regulated

Values are typical and do not constitute a specification.

Packaging

This working solution is prepared on site from Grease Check Concentrate (standard packaging: 275-gallon IBC tote; other formats upon request).

The Grease Check System

The same concentrate also produces **Grease Check Industrial** (1:3, heaviest soils) and **Grease Check Heavy Duty** (1:6, routine degreasing). A Technical Data Sheet and Safety Data Sheet are available for each product in the system.

Storage and Shelf Life

Store in the original closed container at 50–90°F (10–32°C) in a dry, well-ventilated area. Keep from freezing; avoid prolonged storage above 100°F (38°C). Shelf life: 2 years from date of manufacture in the original unopened container. Working solutions are best prepared as needed and used within a reasonable period.

Health and Safety

This product is not classified as hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). Before use, read the Safety Data Sheet for Grease Check Multipurpose (LKA-SDS-004), available from LKA Industrial Solutions Inc. Safety glasses are recommended; wear chemical resistant gloves during prolonged or repeated contact.

LKA Industrial Solutions Inc • 826 Spinnaker Drive East, Hollywood, FL 33019 US • Phone: +1 (754) 314-7507

Disclaimer: The information contained in this Technical Data Sheet is believed to be accurate as of the date of publication and is offered in good faith. Since conditions of use are beyond our control, no warranty, express or implied, is made; users should determine the suitability of the product for their particular application before use.